BioGrease PPG

BIODEGRADABLE PLUNGER PACKING GREASE

DESCRIPTION:

BioGrease PPG is specifically designed for plunger packing lubrication of triplex and quintuplex pumps. **BioGrease PPG** is made from a high quality vegetable oil base with a special blend of polymers to provide low temperature pumpability, excellent adhesion to the plunger, and minimize friction while providing an excellent seal in the system. Pumpability is critical in these pumps and **BioGrease PPG** offers excellent performance at a very wide range of temperatures. In addition, this ultra-low toxicity grease is made from bio-based, sustainable base stocks, and is ultimately biodegradable if released in the environment.

FEATURES:

- Made from renewable, biobased vegetable feedstocks.
- Excellent pumpability and lubricity at a wide range of temperatures.
- Excellent lubrication of plunger and pump components.
- Ultra-low toxicity.
- Ultimately biodegradable per ASTM D5864.
- Naturally protects against corrosion.

| BioGrease | | PPG ^{oo} | PPG ^o | PPG ¹ | |
|---------------------------|------------------|-------------------|------------------|-------------------------|--|
| NLGI Grade: | | 00 | 0 | 1 | |
| Penetration: | ASTM D217 | 410-430 | 355-385 | 310-340 | |
| Thickener Type: | | Lithium 12 | Lithium 12 | Lithium 12 | |
| Color: | Visual | Amber | Amber | Amber | |
| Texture: | | Smooth | Smooth | Smooth | |
| Viscosity: | | | | | |
| @40C, cSt: | ASTM D445 | 100 | 27.5 | 64.6 | |
| @100C, cSt: | ASTM D445 | 21 | 6.2 | 14.03 | |
| Viscosity Index: | ASTM D2270 | 237 | 185.7 | 227 | |
| Flash Point - °F (°C): | ASTM D92 | 520 (271) | 510 (266) | 510 (266) | |
| Fire Point - °F (°C): | ASTM D92 | 550 (287) | 510 (266) | 510 (266) | |
| Copper Corrosion: | ASTM D4048 | 1A | 1A | 1A | |
| Aquatic Toxicity: | ASTM D6046 | Pass | Pass | Pass | |
| Biodegradability: | ASTM D5864 | Pass | Pass | Pass | |
| Rust Test: | ASTM D6046 | Pass | Pass | Pass | |
| Aquatic Toxicity, Fathead | | | | | |
| Minnow, LC50, 96hrs., ppm | EPA-821-R-02-012 | >15,000 | >15,000 | >15,000 | |

TECHNICAL DATA:

AVAILABLE PACKAGING:

35 lb. Pails, 120lb Kegs.



BIOBLEND[™] RENEWABLE RESOURCES LLC 2439 REEVES ROAD - JOLIET, IL 60436 PHONE: 630.227.1800 www.bioblend.com