

SynGrease XT

SYNTHETIC EXTREME TEMPERATURE GREASE

DESCRIPTION:

SynGreaseXT (Extreme Temperature) is a grease formulated to provide superior performance in the toughest conditions. **SynGreaseXT** is formulated with synthetic esters that enable the products to protect equipment at a very wide temperature range while also having limited impact on the environment. The grease provides excellent protection for equipment without using Moly to further reduce its impact on the environment and to enhance its cold weather performance. **SynGreaseXT¹** has mobility at temperatures as low as -40C.

FEATURES:

- ◆ Formulated with high quality synthetic esters.
- ◆ Protects equipment across a wide temperature range.
- ◆ Limited impact on environment.
- ◆ Excellent mobility at low temperatures.
- ◆ Superior equipment protection.

TECHNICAL DATA:

	SynGrease	XT ¹				
NLGI Grade:		1				
Thickener Type:		Lithium				
Texture;		Smooth				
Biodegradability, %:	OECD 301B	>62				
Viscosity:						
@ 40°C, cSt:	ASTM D445	100				
@ 100°C, cSt:	ASTM D445	15				
Viscosity Index:	ASTM D2270	157				
Timken OK Load:	ASTM D2509	80lb pass				
Dropping Point (Min), °F (°C):	ASTM D2265	368 (187)				
4 Ball Weld (Kg):	ASTM D2596	250				
4 Ball Average Scar (mm):	ASTM D2266	.61				
Rust Test:	ASTM D665	3 pass				

AVAILABLE PACKAGING:

35lb. Pails, 120lb Kegs, 400lb. Drums



BIOBLEND™ RENEWABLE RESOURCES LLC
2250 ARTHUR AVE. - ELK GROVE VILLAGE, IL 60007
PHONE: 630.227.1800
www.bioblend.com

6/18/2013

S-SL.LFC.TDS